



# University Department of Yoga Ranchi University, Ranchi

[www.ranchiuniversityyoga.in](http://www.ranchiuniversityyoga.in)

Ref...R.U./P.A.D.Y./L-153

Date...29/01/2020

## Quotation Tender

University Department of Yoga, Facilitation Centre (Behind Aryabhata Hall), Basic & Applied Science Campus, Morabadi Ranchi – 834008 invites sealed quotation tender of following items :

SL.NO	ITEM NAME	QTY	SPECIFICATION
1	Steel Almirah	01	As Annexure 'A'
2	Glass Almirah	01	As Annexure 'A'

The quotation tender envelop must be clearly highlighted with the heading "Quotation for (Name of item)" separately in Technical and Financial Bids. It has to be submitted in the office of University Department of Yoga (Address as mentioned above) till 7th February, 2019 at 2.00 pm. It shall be opened on the same date at 3.00 pm in the office.

  
29/01/2020  
DIRECTOR  
Director  
PG Dept. of Yoga  
R.U., Ranchi

Display at :

1. Website of Yoga department: [www.ranchiuniversityyoga.in](http://www.ranchiuniversityyoga.in)
2. Notice board of the department.



# University Department of Yoga

## Ranchi University, Ranchi

[www.ranchiuniversityyoga.in](http://www.ranchiuniversityyoga.in)

Ref...RU.PG.DY/L-153

Date 29/01/2020

### Annexure-A

#### Specification of Glass Almirah (Qty.: 01 nos.)

Size: 1742 (H) X 914 (W) X 320 (D) mm

1. Four Doors Book Case
2. Distance between each shelf will be 330 mm.
3. 4 mm Thick transparent glass for Each Door for clear inside vision.
5. Every Door should be with locking arrangement with Keys.
6. The thickness of the Book Case sheet shall be 18 SWG.
7. The body of the Book Case shall be manufactured from cold rolled MS sheet (C. R. Sheet) with Anti-rust treatment and shall be finished with powder coating.

#### Specification of Steel Almirah (Qty. 12 nos.)

Size: 2000 (H) X 900 (W) X 450 (D) mm

1. Internal Size of Almirah: 1850 (H) X 900 (W) X 450 (D) mm
2. Leg Size of Almirah: 150 (H) X 120 (W) X 450 (D) mm
3. Rack with 5 no. of shelves. Distance between each shelf will be 360 mm. These 4 shelves should be hanging arrangement (adjustable).
4. Standard lock and 2 sets of keys.
5. The thickness of the Almirah sheet shall be 18 SWG.
6. The body of the Almirah shall be manufactured from cold rolled MS sheet (C. R. Sheet) with Antirust treatment and shall be finished with powder coating.